
# Historic, Archive Document

Do not assume content reflects current scientific knowledge, policies, or practices.



63 99 Jd

UNITED STATES DEPARTMENT OF AGRICULTURE BUREAUS OF ENTOMOLOGY AND PLANT INDUSTRY.

Peach Pest Laboratory, Fort Valley, Georgia.

1926.

SFRAY SCHEDULE FOR GEORGIA PEACHES.

## FIRST APPLICATION.

When 75% of the petals (pink partof flower) have fallen:

One pound powdered arsenate of lead, plus milk of lime made from three pounds of stone lime, to each 50 gallons of water.

## SECOND APPLICATION.

When calyces or "shucks" are shedding, or when small peaches are exposed: One pound powdered arsenate of lead, plus milk of lime made from three pounds of stone lime, to each 50 gallons of water.

## THIRD APPLICATION.

Two weeks after the second application, or about four weeks after the petals have been shed:

Self-boiled lime-sulphur, 8-8-50, alone. (No arsenate of lead in this application).

## FOURTY APPLICATION.

Four weeks before each variety is due to ripen:

One pound powdered arsenate of lead to each 50 gallons of 8-8-50 self-boiled lime-sulphur.

EARLY VARIETIES:

These should be sprayed three times. Use the materials recommended for the 1st, 2nd, and 4th applications above, applying them at the time as noted above. For added protection against brown rot, self-boiled lime-sulphur should also be used in the second application on the early varieties.

#### DIRECTIONS FOR PREPARING THE SPRAY MATERIALS.

The 8-8-50 self-boiled lime-sulphur called for in the spraying schedule is made as follows:

Place 8 pounds of unslaked or stone lime in a 50 gallon barrel, and pour over it enough water, preferably warm, to start the slaking. As the slaking starts, add 8 pounds of sulphur. Add water from time to time to keep the mixture from becoming dry, but care should be exercised not to drown the lime, which would cause the slaking process to stop too soon. After the mixture has boiled some five minutes, cool off with water, strain into the spray tenk, and dilute with water to make 50 gallons. The mixture should be cooled off before the red streaks occur in the mixture to any extent, which is an indication of overheating. Avoid underheating, however. Better results will be obtained by crushing all lumps of sulphur and mixing it with a little water before adding to the slaking lime.

2000

CONTRACT CANADA A A NAME OF A STATE

# 17 1 17 1 FEET

Lord of memorate distribution with a second control of the second

ANTEN A SER OF THE

in carada a la

The contract of the state of th

AND PLEME & CAL

The secretary past responding to the control of the secretary dead profession of the secretary dead profession of the secretary dead of the secretary dead

A CONTRACT C

TO KINDLEY TO FOR THE PARTY TO A COLOR OF STORY

a programme transprouss on the last one or grownest built delice. And it will be

in the content of the

The above formula may be raised to 16-16-100 or 32-32-200. A large container should be used, however, in preparing self-boiled lime-sulphur with these formulae. Stock solutions can of course be made up, observing the proportions given.

The powdered arsenate of lead, which is used in the proportion of 1 pound to 50 gallons of the spray solution, should first be made into a thin paste with water before adding to the spray tank.

1926.

#### DUSTING SCHEDULE FOR GEORGIA PEACHES.

## FIRST APPLICATION.

When 75% of the petals (pink part of flower) have fallen:

Arsenate of lead 5%; lime 95%. \*

## SECOND APPLICATION.

When calyces or #shucks" are shedding, or when small peaches are exposed: Arsenate of lead 5%; lime 95%. \*

## THIRD APPLICATION.

Two weeks after the second application, or about four weeks after the petals have been shed.

Sulphur 80%; arsenate of lead 5%; lime 15%.

## FOURTH APPLICATION.

:

Four weeks before each variety is due to ripen:

Sulphur 80%; arsenate of lead 5%; lime 15%.

EARLY VARIETIES:

Early varieties need only three dust applications, using the formula containing arsenate of lead and lime at the time indicated for the 1st dusting above, and the formula containing sulphur at the time indicated for the 2nd and 4th dustings above.

\* It is not necessary to use sulphur in the first two applications, although the regular formula (80-5-15) may be used if desired.

esta de la companya La companya de la co La companya de la companya del companya de la companya de la companya del companya de la companya del companya de la companya de la companya de la companya del companya de la companya del companya de nother than the second second